



**[TWO POLE DISTRIBUTION BLOCKS]**

This series distribution blocks have two independent poles, between different poles there is a transparent partition plate to keep the connection safe. Meanwhile the covers can be removed during wiring, which provides better convenience.



Open the Cover



FJ-207/125BE



FJ-211/125BE



FJ-215/125BE

CERTIFICATION	CB/CE/RoHS		
<b>MATERIAL</b>			
Size(mm)	50x64x50		
Screw	Zinc-Coated Steel		
Conductor	Brass		
Housing	PA66/V-0		
Cover	PC		
<b>ELECTRICAL DATA</b>			
Standards	IEC 60947-7-1		
Voltage(V)	500		
Current(A)	125		
Icw(KA)	4.5		
IPk(KA)	20		
<b>WIRING DATA</b>	A	B	C
Input	A	B	C
Connection Points	x1		
Torque(N·m)	2~3		
Diameter(mm)	8.5		
Rigid Wire(mm <sup>2</sup> )	10~35		
Flexible Wire(mm <sup>2</sup> )	10~16		
Output	A	B	C
Connection Points	x1	x5	
Torque(N·m)	2~3	2~3	
Diameter(mm)	7.5	5.3	
Rigid Wire(mm <sup>2</sup> )	10~25	2.5~6	
Flexible Wire(mm <sup>2</sup> )	6~16	1.5~6	
<b>PACKING</b>			
Pcs/Inner Box	2		
Pcs/Master Carton	144		

CERTIFICATION	CB/CE/RoHS		
<b>MATERIAL</b>			
Size(mm)	50x100x50		
Screw	Zinc-Coated Steel		
Conductor	Brass		
Housing	PA66/V-0		
Cover	PC		
<b>ELECTRICAL DATA</b>			
Standards	IEC 60947-7-1		
Voltage(V)	500		
Current(A)	125		
Icw(KA)	4.5		
IPk(KA)	20		
<b>WIRING DATA</b>	A	B	C
Input	A	B	C
Connection Points	x2		
Torque(N·m)	2~3		
Diameter(mm)	8.5		
Rigid Wire(mm <sup>2</sup> )	10~35		
Flexible Wire(mm <sup>2</sup> )	10~16		
Output	A	B	C
Connection Points	x2	x7	
Torque(N·m)	2~3	2~3	
Diameter(mm)	7.5	5.3	
Rigid Wire(mm <sup>2</sup> )	10~25	2.5~6	
Flexible Wire(mm <sup>2</sup> )	6~16	1.5~6	
<b>PACKING</b>			
Pcs/Inner Box	1		
Pcs/Master Carton	84		

CERTIFICATION	CB/CE/RoHS		
<b>MATERIAL</b>			
Size(mm)	50x130x50		
Screw	Zinc-Coated Steel		
Conductor	Brass		
Housing	PA66/V-0		
Cover	PC		
<b>ELECTRICAL DATA</b>			
Standards	IEC 60947-7-1		
Voltage(V)	500		
Current(A)	125		
Icw(KA)	4.5		
IPk(KA)	20		
<b>WIRING DATA</b>	A	B	C
Input	A	B	C
Connection Points	x2		
Torque(N·m)	2~3		
Diameter(mm)	8.5		
Rigid Wire(mm <sup>2</sup> )	10~35		
Flexible Wire(mm <sup>2</sup> )	10~16		
Output	A	B	C
Connection Points	x2	x11	
Torque(N·m)	2~3	2~3	
Diameter(mm)	7.5	5.3	
Rigid Wire(mm <sup>2</sup> )	10~25	2.5~6	
Flexible Wire(mm <sup>2</sup> )	6~16	1.5~6	
<b>PACKING</b>			
Pcs/Inner Box	1		
Pcs/Master Carton	72		